

AD 2 AERODROMES**ESTA 2.1 AERODROME LOCATION INDICATOR AND NAME****ESTA – ÄNGELHOLM****ESTA 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA**

- | | | |
|----|--|---|
| 1. | ARP coordinates and site at AD | 561728N 0125118E RWY 14/32 centre point |
| 2. | Direction and distance from (city) | N 4 NM from Ängelholm |
| 3. | Elevation/Reference temperature | 60 ft/+18.5°C |
| 4. | Geoid undulation at AD ELEV PSN | 121 ft |
| 5. | MAG VAR/Annual change | 3° E 2015/+0.1 increasing |
| 6. | Administration, address, telephone, fax, AFS | Ängelholms flygplats AB
Ängelholm Helsingborg Airport
SE-262 91 Ängelholm
TEL: +46 (0)431 48 45 00
FAX: +46 (0)431 48 45 10
E-mail: info@angelholmhelsingborgairport.se
AFS: ESTAZTZX
Website: www.angelholmhelsingborgairport.se |
| 7. | Types of traffic permitted (IFR/VFR) | IFR/VFR. Max RWY ref code 4C |
| 8. | Remarks | PPR outside TWR hours. Request shall be made during AD Administration hours. Mail: ok@aghairport.se .

PPR for IFR school and training flights at all times. For request during TWR hours call ATC +46 (0)431 202 14. |

ESTA 2.3 OPERATIONAL HOURS

- | | | |
|-----|---|---|
| 1. | AD Administration
AD Operating hours | MON-FRI 0700-1500 (0600-1400)
As ATS |
| 2. | Customs and immigration | O/R TEL +46 (0)40 661 32 20 |
| 3. | Health and sanitation | - |
| 4. | AIS Briefing Office | FPC H24, +46 (0)8 797 63 40, www.lfv.se/fpc |
| 5. | ATS Reporting Office (ARO) | As ATS |
| 6. | MET Briefing Office | FPC H24, +46 (0)8 797 63 40, www.lfv.se/fpc |
| 7. | ATS | Ref AIP SUP/NOTAM |
| 8. | Fuelling | As ATS |
| 9. | Handling | As ATS |
| 10. | Security | O/R |
| 11. | De-Icing | As ATS |
| 12. | Remarks | Increased charges outside AD Operating HR of OPS |

ESTA 2.4 HANDLING SERVICES AND FACILITIES

- | | | |
|----|--|---|
| 1. | Cargo-handling facilities | - |
| 2. | Fuel/oil types | Fuel 100 LL, Jet A1
Oil - |
| 3. | Fuelling facilities/discharge capacity | 100 LL: 10,000 l stationary
Jet A1: 100,000 l fuel truck and hydrant |
| 4. | De-icing facilities | Available Type I and II, mobile unit |
| 5. | Hangar space for visiting ACFT | - |
| 6. | Repair facilities for visiting ACFT | - |
| 7. | Remarks | Fuel supplier: AirBP |

ESTA 2.5 PASSENGER FACILITIES

- | | | |
|----|----------------------|---------------------------|
| 1. | Hotels | In Ängelholm |
| 2. | Restaurants | In Ängelholm |
| 3. | Transportation | Buses, taxis, rental cars |
| 4. | Medical facilities | In Ängelholm |
| 5. | Bank and Post Office | In Ängelholm |
| 6. | Tourist Office | In Ängelholm |
| 7. | Remarks | - |

ESTA 2.6 RESCUE AND FIRE FIGHTING SERVICES

- | | | |
|----|---|---|
| 1. | AD category for fire fighting | CAT 6. For commercial traffic exceeding 2500 kg MTOW 180 sec,
other traffic 8 min. |
| 2. | Rescue equipment | By arrangement |
| 3. | Capability for removal of disabled aircraft | By arrangement |
| 4. | Remarks | - |

ESTA 2.7 SEASONAL AVAILABILITY – CLEARING

- | | | |
|----|-----------------------------|---|
| 1. | Types of clearing equipment | Snowploughs, blowers, sweepers, spreaders |
| 2. | Clearance priorities | RWY, TWY, Apron |
| 3. | Remarks | - |

ESTA 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS DATA

- | | | |
|----|-------------------------------------|--|
| 1. | Apron surface and strength | Apron B ASPH PCN 25 F/C/X/T
Apron D ASPH PCN 25 F/C/X/T
Apron E ASPH PCN 45 F/C/X/T
Apron W ASPH PCN 45 F/C/X/T |
| 2. | Taxiway width, surface and strength | TWY A 18 m ASPH PCN 45 F/C/X/T
TWY C 18 m ASPH PCN 45 F/C/X/T
TWY E 10 m CONC PCN 25 R/C/X/T
TWY F 18 m ASPH PCN 45 F/C/X/T
TWY G 15 m ASPH PCN 25 F/C/X/T
TWY J 10 m CONC PCN 25 R/C/X/T
TWY M 10 m CONC PCN 25 R/C/X/T |
| 3. | ACL, location and elevation | Apron E 50 ft |
| 4. | VOR checkpoints | - |
| 5. | INS checkpoints | - |
| 6. | Remarks | TWY F Distance to beginning of RWY 32 is 100 m |

ESTA 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

- | | | |
|----|---|---|
| 1. | Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of ACFT stands | Taxi guide lines and signs. Marshalling available |
| 2. | RWY and TWY markings and LGT | <p>RWY 14/32: Designator, THR, TDZ, CL and edges are day marked
RTHL, REDL, RENL</p> <p>TWY A: CL, HLDG day marked. Edge lights, RGL
C: CL, HLDG day marked. Edge lights, RGL
E: CL, HLDG day marked. Edge lights
F: CL, HLDG day marked. Edge lights, RGL
G: CL, HLDG day marked. Edge lights, RGL
J: CL, HLDG day marked. Edge lights
M: CL, HLDG day marked. RGL</p> |
| 3. | Stop bars | - |
| 4. | Remarks | - |

ESTA 2.10 AERODROME OBSTACLES

In Area 2					
OBST ID/Designation	OBST type	OBST position	ELEV/HGT	Markings/ Type, colour	Remarks
a	b	c	d	e	f
Not available					

In Area 3					
OBST ID/Designation	OBST type	OBST position	ELEV/HGT	Markings/ Type, colour	Remarks
a	b	c	d	e	f
Not available					

ESTA 2.11 METEOROLOGICAL INFORMATION PROVIDED

1. Associated MET Office STOCKHOLM/Arlanda
2. Hours of service H24
MET Office outside hours
3. Office responsible for TAF preparation STOCKHOLM/Arlanda
Periods of validity 9 HR HO
4. Type of landing forecast Not issued
Interval of issuance
5. Briefing/consultation provided FPC H24, +46 (0)8 797 63 40, www.lfv.se/fpc
6. Flight documentation TAF, METAR, SIGMET, Upper air winds
Language(s) used Swedish/English
7. Charts and other information available for SWC, WC, Nordic SIGWX Chart, Low level forecast
briefing or consultation
8. Supplementary equipment available for -
providing information
9. ATS units provided with information ÄNGELHOLM TMC
ÄNGELHOLM TWR
10. Additional information (limitation of service, Flight planning room available at apron W
etc.)

ESTA 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	True BRG and MAG BRG	Dimensions of RWY (m)	Strength (PCN) and surface of RWY and SWY	THR coordinates RWY end coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APCH RWY
1	2	3	4	5	6
14	136.37° GEO 133° MAG	1945 x 45	PCN 45 F/C/X/T ASPH	561752.12N 0125039.16E GUND 121 ft	THR 59.7 ft TDZ 60 ft
32	316.39° GEO 313° MAG	1945 x 45	PCN 45 F/C/X/T ASPH	561706.60N 0125157.17E GUND 121 ft	THR 52 ft

Slope of RWY-SWY	SWY dimensions (m)	CWY dimensions (m)	Strip dimensions (m)	OFZ	Remarks
7	8	9	10	11	12
14 See ESTA AOC	-	-	2065 x 300	-	-
32 See ESTA AOC	-	205 x 180	2065 x 300	-	-

ESTA 2.13 DECLARED DISTANCES

RWY Designator	TORA (m)	TODA (m)	ASDA (m)	LDA (m)	Remarks
1	2	3	4	5	6
14	1945	1945	1945	1945	-
32	1945	2150	1945	1945	-

ESTA 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT Type, LEN INTST	THR LGT Colour WBAR	VASIS (MEHT)	TDZ LGT LEN	RWY Centre Line LGT LEN, Spacing Colour INTST	RWY Edge LGT LEN, Spacing Colour INTST	RWY End LGT Colour WBAR	SWY LGT LEN, Colour
1	2	3	4	5	6	7	8	9
14	Barrette CL CAT I 900 m LIH	Green	PAPI Left/3.00° (37.4 ft)	-	-	1945/60 m White Caution zone 600 m yellow LIH	Red	-
32	SALS 420 m LIH	Green	PAPI Left/3.00° (54.1 ft)	-	-	1945/60 m White Caution zone 600 m yellow LIH	Red	-
10 Remarks: -								

ESTA 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1. ABN/IBN location, characteristics and hours of operation -
2. LDI location and LGT -
Anemometer location and LGT At RWY ends, lighted
3. TWY edge and centre line lighting Edge: TWY A, C, E, F, G, J
CL: -
4. Secondary power supply/switch-over time Available/1 sec
5. Remarks -

ESTA 2.16 HELICOPTER LANDING AREA

RWY 14/32 to be used

ESTA 2.17 ATS AIRSPACE

1. Designation and lateral limits ÄNGELHOLM CTR 562721N 0124021E - 562259N 0130320E -
561300N 0130602E - 560930N 0130004E -
561244N 0124651E - 561459N 0124251E -
562258N 0123255E - 562721N 0124021E
2. Vertical limits ÄNGELHOLM CTR 1500 ft AMSL
GND
3. Airspace classification C
4. ATS unit call sign ÄNGELHOLM TOWER
Language(s) Swedish/English
5. Transition altitude 5000 ft AMSL
6. Remarks CTR established during hours of TWR.

ESTA 2.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Frequency	Hours of operation	Remarks
1	2	3	4	5
TWR	ÄNGELHOLM TOWER	127.100 MHz	HO	Primary FREQ
		121.500 MHz	HO	-
TMC	ÄNGELHOLM CONTROL	132.450 MHz	HO	-

ESTA 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid CAT of ILS/MLS (for VOR/ILS/MLS give VAR)	ID	Frequency	Hours of operation	Site of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
LOC 14 ILS CAT II (3° E 2015)	DB	111.30 MHz	H24	561657.7N 0125212.4E		380 m beyond THR 32 ILS Class II/D/3
GP		332.30 MHz	H24	561747.4N 0125057.0E		Angle 3.0° RDH 51 ft 316 m past THR 14 left side
L 14	LB	370.5 kHz	H24	562047.6N 0124559.1E		Range 25 NM
L 32	AH	417 kHz	H24	561558.1N 0125402.6E		Range 15 NM
DME	DB	111.30 MHz	H24	561747.6N 0125057.3E	91 ft	DME channel 50X

ESTA 2.20 LOKALA TRAFIKFÖRESKRIFTER

- Dagligen mellan 2100 och 0500 (2000–0400) får flygplatsen inte trafikeras med flygplan certifierade enligt ICAO Annex 16, Volume I, Part II, Chapter 2.
- Högervarv tillämpas när RWY 32 är i användning.
- Upprepade instrumentinflygningar samt TGL tillåts endast efter PPR och på följande tider:
MON–THU 0730–1900 (0630–1800)
FRI 0730–1600 (0630–1500)
SAT, SUN, HOL 0900–1600 (0800–1500)
- På parkeringsplats får APU användas endast när så krävs för motorstart eller för reglering av kabinvärme. APU får därvid inte startas tidigare än 15 min före beräknad tid för taxning.

LOCAL TRAFFIC REGULATIONS

- Daily between 2100–0500 (2000–0400) the aerodrome must not be used by aircraft certificated in accordance with ICAO Annex 16, Volume I, Part II, Chapter 2.
- Right hand traffic circuit when RWY 32 is in use.
- Repeated instrument approaches and TGL accepted after PPR only and during the following hours:
MON–THU 0730–1900 (0630–1800)
FRI 0730–1600 (0630–1500)
SAT, SUN, HOL 0900–1600 (0800–1500)
- On parking stand APU shall not be operated unless required for engine start or adjustment of cabin heat. In no case APU may be started earlier than 15 min before estimated time for taxiing.

ESTA 2.21 MINSKNING AV BULLERSTÖRNING

- Över de centrala delarna av Ängelholm bör luftfartyg inte framföras på lägre höjd än 2000 ft AMSL utom då så är nödvändigt i samband med start och landning.
- Angivna flygvägar för ankommande och avgående trafik har upprättats även för att minska bullerstörningar. Luftfartyg skall noggrant följa i klareringen angiven flygväg samt i övrigt framföras så att onödiga bullerstörningar inte förorsakas.

NOISE ABATEMENT PROCEDURES

- Over the central parts of Ängelholm aircraft should not be operated below 2000 ft AMSL except when necessary for take-off or landing.
- The routes for inbound and outbound traffic have been established also for noise abatement purposes. Aircraft shall strictly adhere to assigned route and be operated in such a manner that unnecessary noise disturbances are not caused.

ESTA 2.22 FLYGPROCEDURER

1. Ankommande IFR-trafik inom Ängelholm TMA/CTR

Flygvägar

Se sid ESTA-4-5 till ESTA-4-10.

2. Startprocedurer, omnidirectional

FLIGHT PROCEDURES

1. Inbound IFR traffic within Ängelholm TMA/CTR

Routes

See pages ESTA-4-5 through ESTA-4-10.

2. Omnidirectional departure procedures

RWY	Procedure	Significant obstacle		
		Obstacle	Elevation (ft)	Direction (GEO)/Dist (m) from THR
14	Climb straight ahead to MNM turning ALT 600 ft. Continue climb to appropriate MSA.	-	-	-
32	Climb straight ahead to MNM turning ALT 800 ft. Continue climb to appropriate MSA.	Tree	675	353°/9000

3. Avbrott i radioförbindelse

Luftfartyg skall följa de föreskrifter som anges i AIP ENR 1.3 mom 9.

4. Lågsiktsprocedurer (LVP)

LVP finns etablerade och träder ikraft senast om RVR är lägre än 550 m och/eller molnbasen är lägre än 200 ft eller på begäran. Meddelande om att LVP tillämpas lämnas av ATS.

När LVP tillämpas tillåts endast ett luftfartyg eller fordon inom LVP-området (manöverområdet enl AD 2 ESTA 2-1).

5. VFR flygning inom Ängelholm TMA/CTR

Normala in- och utpasseringspunkter
Se ESTA 6-1.

Väntlägen

Se ESTA 6-1.

6. Inflygningsprocedur Annan än standard

Speciell inflygningsprocedur Annan än standard CAT II RWY 14 tillgänglig på begäran.

Lågsiktsprocedurer skall vara i kraft.

Godkännande för användning av Annan än standard CAT II krävs av Transportstyrelsen och för utländska operatörer deras nationella flygsäkerhetsmyndighet.

3. Communication failure

Aircraft shall follow the procedures laid down in AIP ENR 1.3 para 9.

4. Low visibility procedures (LVP)

LVP are established and will be in force at latest when RVR falls below 550 m and/or the cloudbase is less than 200 ft or on request. The application of LVP will be announced by ATS.

When LVP is applied only one aircraft or vehicles are allowed in the LVP area (same as manoeuvring area on AD 2 ESTA 2-1).

5. VFR flight within Ängelholm TMA/CTR

Normal entry and exit points
See ESTA 6-1.

Holding points

See ESTA 6-1.

6. Approach procedure Other Than Standard (OTS)

Special approach procedure Other Than Standard (OTS) CAT II RWY 14 available on request.

Low visibility procedures (LVP) shall be in force.

Authorization for Other Than Standard (OTS) Category II operations by the operator's National Aviation Authority is required.

ESTA 2.23 ÖVRIG INFORMATION

NIL

ADDITIONAL INFORMATION

NIL

ESTA 2.24 TILLHÖRANDE KARTOR**RELATED CHARTS**

AD chart		ESTA 2-1
AOC	RWY14/32	ESTA-3-1
PATC	RWY 14	ESTA-3-3
Area chart (TMA)		ESTA 4-1
List of waypoints and significant points		ESTA 4-3
RNAV (GNSS) STAR	RWY 32	ESTA-4-5
STAR RWY 14		ESTA-4-7
STAR RWY 32		ESTA-4-9
ATC Surveillance		ESTA 4-91
Minimum ALT chart		
IAC	ILS Cat I or LOC RWY 14	ESTA-5-1
IAC	ILS OTS Cat II RWY 14	ESTA-5-2
IAC	NDB RWY 14	ESTA-5-3
IAC	NDB RWY 32	ESTA-5-4
IAC	RNAV (GNSS) RWY 32	ESTA-5-5
VAC		ESTA 6-1